

## 1080P AHD Color Dome Camera

- Video Output: AHD 1080P / AHD 720P / TVI / CVI / CVBS
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance–Coaxial cable (3C/5C): 300M / 500M, Twisted cable: 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux
- UTC function (AHD-Coaxial protocol)

Pick Up Element	1/2.9" CMOS Image Sensor
Effective pixels	1,985 (H) × 1,105 (V)
Scanning System	Progressive Scan
Lens	2.8mm/3.6mm
Iris	F2.0
Angle of View	(H)102°(V)72°(D)140°
Min. illumination/Low Light Mode (Colour)	0.03 Lux / F1.8
White Balance	ATW /MANUAL
Electrical Shutter	Auto : 1/60(1/50)S – 1/50,000S
Sense Up	OFF / AUTO (X2 – X30)
Auto Gain Control	Auto
S / N Ratio	More Than 55dB (AGC Off)
3D Noise Reduction	2DNR
2D WDR	OFF / ON
Video output	AHD1080P / AHD720P / TVI / CVI / CVBS
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
UTC	AHD-Coaxial protocol Supported
Languages	ENGLISH,中文(簡),ESPAÑOL,FRANCAIS,繁中,PYCKCKNN,ITALIANO,EAAHNIKA,한국어,日本語,PORTUGUES ,POLISH
Operating temperature	- 10°C – + 50°C ( -14°F – 122°F )
Dimensions	Ø120 × 102mm(H)
Weight	305g
Power Supply	DC12V ±10%
Power Consumption	0.85W