

## D/N VR 1080P AHD VARI-FOCAL DOME IR Camera

- Video Output: AHD 1080P / AHD 720P / TVI / CVI / CVBS
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance–Coaxial cable (3C/5C): 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux
- High efficiency IR LED, radiant distance up to 20M
- "Up The Coax." AHD camera supported

Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Infrared Cut Filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
S / N Ratio	More Than 55dB (AGC Off)
Pick Up Element	1/2.9" CMOS Image Sensor
Effective pixels	1,985 (H) × 1,105 (V)
Scanning System	Progressive Scan
Min. illumination/Low Light Mode (Colour)	0.02 Lux / F1.4, 0 Lux (IR On)
Lens	2.8 – 12mm
Iris	F1.4
Angle of View	(H)91° - 28°。 (V)67.5° - 21.2°。 (D)120.8° - 36°
Max IR distance	20M
Infrared LED Angle	30°
Peak wavelength	850nm
Auto Gain Control	Auto
White Balance	ATW / AWC / INDOOR / OUTDOOR / MANUAL / AWB
3D Noise Reduction	2DNR
2D WDR	OFF / ON
IP Rating	IP67
Vandal Resistant Rating / IK Rating	IK10
Video output	AHD 1080P / AHD 720P / TVI / CVI / CVBS
System	NTSC or PAL
Menu Control	OSD Control
Sync. Mode/	Internal

## D/N VR 1080P AHD VARI-FOCAL DOME IR Camera

Synchronization	
UTC	AHD-Coaxial protocol Supported
Electrical Shutter	Auto 1/60(1/50)S – 1/50,000S
Languages	ENGLISH,中文(簡),ESPAÑOL,FRANCAIS,繁 中,РУССКИЙ,ITALIANO,ΕΛΛΗΝΙΚΑ,한국어,日本 語,PORTUGUES ,POLISH
Operating temperature	- 40°C – + 50°C ( -40°F – 122°F )
Dimensions	Ø145(D) × 130mm(H)
Weight	1000g
Power Supply	DC12V ±10%
Power Consumption	4.3W