

D/N 1080P AHD VARI-FOCAL VR DOME IR Camera

- Video Output: AHD 1080P / AHD 720P / TVI / CVI / CVBS
- Video without compression, no delay with high quality and real-time monitoring
- Long transmission distance—Coaxial cable (3C/5C): 300M / 500M, Twisted cable: 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Below 10Lux
- UTC function (AHD-Coaxial protocol)

Resolution	1,920 (H) x 1,080 (V) @ 30/25 fps
Lens	2.8 - 12mm
Iris	F1.4
Angle of View	(H)91° - 28°(V)67.5° - 21.2° (D)120.8° - 36°
Max IR distance	20M
Infrared LED Angle	30°
Peak wavelength	850nm
Pick Up Element	1/2.9" CMOS Image Sensor
Effective pixels	1,985 (H) × 1,105 (V)
Scanning System	Progressive Scan
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
Infrared Cut Filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
Min. illumination/Low Light Mode (Colour)	0.02 Lux / F1.4, 0 Lux (IR On)
S / N Ratio	More Than 55dB (AGC Off)
UTC	AHD-Coaxial protocol Supported
Auto Gain Control	Auto
White Balance	ATW /MANUAL
Electrical Shutter	(Auto)1/60(1/50)S ~ 1/50,000S
2D WDR	OFF / ON
3D Noise Reduction	2DNR
Languages	ENGLISH,中文(簡),ESPANOL,FRANCAIS,繁 中,PYCKCKNN,ITALIANO,EAAHNIKA,한국어,日本

D/N 1080P AHD VARI-FOCAL VR DOME IR Camera

	語,PORTUGUES ,POLISH
Video output	AHD 1080P / AHD 720P / TVI / CVI / CVBS
Operating temperature	- 40°C – + 50°C (-40°F – 122°F)
IP Rating	IP66
Vandal Resistant Rating / IK Rating	IK10
Dimensions	Ø140(D) × 102mm(H)
Weight	610g
Power Supply	DC12V ±10%
Power Consumption	4.3W

D/N 1080P AHD VARI-FOCAL VR DOME IR Camera