

D/N 1080P AHD VARI-FOCAL IR CAMERA

- Video Output: AHD 1080P / AHD 720P / TVI / CVI / CVBS
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance–Coaxial cable (3C/5C): 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux
- UTC function (AHD-Coaxial protocol)

Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Pick Up Element	1/2.9" CMOS Image Sensor
Effective pixels	1,985 (H) × 1,105 (V)
Scanning System	Progressive Scan
Min. illumination/Low Light Mode (Colour)	0.02 Lux / F1.4, 0 Lux (IR On)
Lens	2.8 - 12mm
Iris	F1.4
Angle of View	(H)91° - 28° (V)67.5° - 21.2° (D)120.8° - 36°
Max IR distance	30M
Infrared LED Angle	30°
Peak wavelength	850nm
Auto Gain Control	Auto
White Balance	ATW /MANUAL
Electrical Shutter	Auto : 1/60(1/50)S ~ 1/50,000S
3D Noise Reduction	2DNR
2D WDR	OFF / ON
IP Rating	IP66
Video output	AHD 1080P / AHD 720P / TVI / CVI / CVBS
Window / Glass Thickness	φ65 Heat Resistant Glass
S / N Ratio	More Than 55dB (AGC Off)
Infrared Cut Filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
System	NTSC or PAL
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
UTC	AHD-Coaxial protocol Supported

D/N 1080P AHD VARI-FOCAL IR CAMERA

Languages	ENGLISH,中文(簡),ESPAÑOL,FRANÇAIS,繁體中文,РУССКИЙ,ITALIANO,ΕΛΛΗΝΙΚΑ,한국어,日本語,PORTUGUES ,POLISH
Operating temperature	- 40°C – + 50°C (-40°F – 122°F)
Dimensions	Body: 82mm (W) × 72.5mm (H) × 154mm (D), Bracket: 101mm (L)
Weight	545g
Power Supply	DC12V ±10%
Power Consumption	4.1W