

D/N 1080P AHD DOME IR Camera

- Video Output: AHD 1080P / AHD 720P / TVI / CVI / CVBS
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance–Coaxial cable (3C/5C): 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux
- High efficiency IR LED, radiant distance up to 16M
- “Up The Coax.” AHD camera supported

Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Pick Up Element	1/2.9" CMOS Image Sensor
Effective pixels	1,985 (H) × 1,105 (V)
Scanning System	Progressive Scan
Min. illumination/Low Light Mode (Colour)	0.03 Lux / F1.8, 0 Lux (IR On)
Lens/ Iris	3.6mm / F2.0
Angle of View	(H)72.2° (V)52.9° (D)94.3°
Infrared LED Angle	30°
Max IR distance	16M
Peak wavelength	850nm
Auto Gain Control	Auto
White Balance	ATW / MANUAL
Electrical Shutter	Auto : 1/60(1/50)S – 1/50,000S
3D Noise Reduction	2DNR
2D WDR	OFF / ON
S / N Ratio	More Than 55dB (AGC Off)
Video output	AHD 1080P / AHD 720P / TVI / CVI / CVBS
Infrared Cut Filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
UTC	AHD-Coaxial protocol Supported
Languages	ENGLISH,中文(簡),ESPAÑOL,FRANCAIS,繁中,РУССКИЙ,ITALIANO,ΕΛΛΗΝΙΚΑ,한국어,日本語,PORTUGUES ,POLISH
Operating temperature	- 10°C – + 50°C (-14°F – 122°F)
Dimensions	Ø93 × 74mm (H)
Weight	230g
Power Supply	DC12V ±10%
Power Consumption	3W