

D/N 1080P AHD IR Camera

- Video Output: AHD 1080P / AHD 720P / TVI / CVI / CVBS
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance–Coaxial cable (3C/5C): 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux
- High efficiency IR LED, radiant distance up to 50M
- “Up The Coax.” AHD camera supported (for 1080P)
- Weatherproof IP66

Resolution	1,920 (H) × 1,080 (V) @ 30 fps
Pick Up Element	1/2.9" CMOS Image Sensor
Effective pixels	1,985 (H) × 1,105 (V)
Scanning System	Progressive Scan
Min. illumination/Low Light Mode (Colour)	0.02 Lux / F1.4, 0 Lux (IR On)
Lens	2.8 – 12mm
Iris	F1.4
Angle of View	(H)91°– 28 (V)67.5°– 21.2° (D)120.8°– 36°
Max IR distance	50M
Infrared LED Angle	30°
Peak wavelength	850nm
Auto Gain Control	Auto
White Balance	ATW / MANUAL
Electrical Shutter	Auto : 1/60(1/50)S – 1/50,000S
3D Noise Reduction	2DNR
2D WDR	OFF / ON
IP Rating	IP66
Video output	AHD 1080P / AHD 720P / TVI / CVI / CVBS
Window / Glass Thickness	Ø72 Heat Resistant Glass
Infrared Cut Filter	Auto Selectable, Automatic Switch from Color Mode to Monochrome
S / N Ratio	More Than 55dB (AGC Off)
Menu Control	OSD Control
Sync. Mode/ Synchronization	Internal
UTC	AHD-Coaxial protocol Supported
Languages	ENGLISH,中文(簡),ESPAÑOL,FRANCAIS,繁

D/N 1080P AHD IR Camera

	中,PYCCCKNN,ITALIANO,EAAHNIKA,한국어,日本語,PORTUGUES ,POLISH
Operating temperature	- 40°C – + 50°C (-40°F – 122°F)
Dimensions	Body : 98.5mm (W) × 90mm (H) × 195mm (D), Bracket: 160mm (L)
Weight	1200g
Power Supply	DC12V ±10%
System	NTSC or PAL
Power Consumption	10.8W