

2MP 20X 150m IR Starlight WDR Network Speedome

Camera	Image Sensor	1/2.8" SONY STARVIS Sensor
	Effective Pixels	1920x1080
	Min. Illumination	0.006Lux Color / 0.003Lux BW (F1.6,
	S/N Ratio	> 50dB
	Shuttle	1/25 ~ 1/100,100 @50Hz
	Day & Night	Filter Change or TDN (True Day & Nig
Lens	Focal Length	20X (5.5~110mm)
	Field Of View	Horizontal : 52°~1.78° ; Diagonal : 5
	Aperture	F1.6 ~ F3.5
Mechanism	Pan Speed	0.5~80°/s Manual, 80°/s Preset
	Tilt Speed	0.5~80°/s Manual, 80°/s Preset
	Presets	255
	Tour	8 Tour (Each with max. 16 Presets)
	Track	4 Track (Each with max. 3min)
	Park Action	Tour, Scan, Track, Preset
Network	Ethernet	10/100 Base-T, RJ45 connector
	Max. Frame Rate	25fps @1920x1080
	Simultaneous Log-in	6
	3-Stream	Support
	SD Storage	Manual / Alarm Rec, up to 128GB, A
	Web Broser	IE 8~11, Chrome 31~44, Firefox 30~5